



# i-B2 BROADCAST TAG



The i-B2 series is the beacon generation of IDEN TEC SOLUTIONS' SensorSMART active RFID tags.

Built on IDEN TEC SOLUTIONS' patented high-performance technology, the i B2 tag provides impressive long-range capabilities for wireless applications that require the benefits provided by beacon tags. Static data is written on an i-B tag and is continuously sent at a programmable interval (ping rate) without being requested by a reader. The i-B2 series offers an attractive price for continuous tag collection in specific scenarios such as:

- Access control
- Tracking of Vehicles and Containers
- Online inventory
- Localization of assets or personnel at spe-

cific areas (i.e. gates, dock doors)

Using advanced UHF radio frequency technology, i-B2 tags send data at distances of up to 100 meters (300 feet) to either a mobile (handheld) or fixed reader (interrogator). Due to the ultra-low power consumption and configurable ping rate (one second to four minutes), the i-B2 tag can effectively operate maintenance-free for many years.

The i-B2 tag is the most economical choice for basic long-range technology and is ideal for tracking mobile assets in more stable, predictable environments.

## BENEFITS

100-meter read range - Allows the longest read-range for identification and tracking using beacon technology.

Long battery lifetime - Delivers long time maintenance-free operation, without battery replacement. The battery lifetime depends on the ping rate, which is configurable.

UHF operating frequencies - Tags are available for both standard North American and European ISM band frequencies.

Non-line-of-sight data transmission - Allows tags to be identified without the need of visual contact.

Automatic transmission - Tags do not have to be "woken" — they transmit automatically.

Customizable ping rate - Durable in demanding environments. Ensures that the frequency band is not busy.

Low cost - Economical choice for tracking assets with active RFID technology.

## FEATURES

- 100-meter read range
- Long battery lifetime
- UHF operating frequencies
- Non-line-of-sight data transmission
- Automatic transmission
- Industrial housing
- Customizable ping rate
- Low cost

Information in this document is subject to change without notice and becomes contractual only after written confirmation by IDEN TEC SOLUTIONS. "IDEN TEC SOLUTIONS", "Intelligent Long Range", "ILR", "i-LINKS", "i-Q", "i-D", "i-B", "i-CARD", "i-PORT", "Solutions. It's in our name.", "Smarten up your assets." and the stylized "i" are trademarks or registered trademarks of IDEN TEC SOLUTIONS, Inc. and/or IDEN TEC SOLUTIONS AG.

Copyright © 2010 by IDEN TEC SOLUTIONS. All rights reserved. Version 1.8 4/12/2010

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.



# i-B2 BROADCAST TAG

IDENTEC SOLUTIONS delivers innovative wireless sensor technology and systems that are helping transform the way business manages industrial processes and safeguards lives.

Committed to developing industry-leading, low power and long-range sensor based solutions, IDENTEC SOLUTIONS' SensorSMART networks have been setting the industry standard since 1999. Currently deployed on every continent throughout the globe in the Marine, Intermodal & Logistics, Oil, Gas & Mining, Construction industries as well as sought out by the world's leading system integrators and governments; IDENTEC SOLUTIONS patented technology is helping to optimize productivity in some of the continent's most challenging situations. Robust, flexible and powerful IDENTEC SOLUTIONS technology delivers when others cannot.

IDENTEC SOLUTIONS is privately held, with its corporate office located in Lustenau, Austria, and North American headquarters in Dallas, Texas, along with service centers in Germany, Australia and Norway. For more information, please visit [www.identecsolutions.com](http://www.identecsolutions.com).

WARNING: Changes or modifications not expressly approved by manufacturer could void the user's authority to operate the equipment. Contents subject to change without notice.

## TECHNICAL SPECIFICATIONS

### Performance

Read range to i-PORT MB	Up to 100 m (300 ft) (free air)*
Read range to i-CARD CF B	Up to 100 m (300 ft) (free air)*
Operating frequency	868 MHz (EC) or 915 MHz (NA) ISM band
Operation	Transmits in regular intervals a pre-programmed data string
Repetition rate (ping rate)	0.5 – 60 seconds in 0.5 second steps
Transmit power	< 1 mW
Certification	CE (EN 300 220-1, -3); ETSI EN 301 489-1, -3), FCC part 15 (US), Industry Canada

\*The communication range depends on the antenna type, the antenna cable runs and the environmental conditions.

### Electrical

Power source	Lithium battery (not replaceable)
Expected battery life	4 Years @ 2 second intervals

### Data

Programming and activation	Wireless by proximity device over a distance of maximum 5 cm
Data size	9 Bytes (user definable)
Identification code	32 bits fixed ID

### Environmental

Operating temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Shock	50 G, 3 times DIN IEC 68-2-27 Multiple drops to concrete from 1 m (3 ft)
Vibration	3 G, 20 sine wave cycles, 5 Hz to 150 Hz, DIN IEC 68-2-6 5 G, noise 5 Hz to 1000 Hz, 30 minutes DIN IEC 68-2-64

### Physical

Dimensions	131 x 28 x 21 mm (5.2 x 1.1 x 0.85 in.)
Case Material	Plastic (Luran® S)
Mass	50 grams (1.75 ounces)
Enclosure rating	IP 65 — Protected against dust and low-pressure jets of water
Color	royal blue

## CONTACT US

**EUROPE**  
+43 5577 87387-0  
[sales@identecsolutions.com](mailto:sales@identecsolutions.com)

**NORTH AMERICA**  
1-866-402-4211 (toll free)  
[sales@identecsolutions.com](mailto:sales@identecsolutions.com)

**HEAD OFFICE**  
IDENTEC SOLUTIONS AG  
Millennium Park 2  
6890 Lustenau  
Austria  
Tel. +43 5577 87387 0  
Fax +49 5577 87387 15

**GERMANY**  
IDENTEC SOLUTIONS  
DEUTSCHLAND GMBH  
Hertzstrasse 10  
69469 Weinheim  
Germany  
Tel.: +49 (0)6201 9957-0  
Fax: +49 (0)6201 9957-99

**USA**  
IDENTEC SOLUTIONS, INC.  
Liberty Plaza II, Suite 375  
5057 Keller Springs Rd,  
Addison, Texas 75001  
USA  
Tel: (972) 535 4144  
Fax: (469) 424-0404

**NORWAY**  
IDENTEC SOLUTIONS AS  
Skarpengland  
4715 ØVREBØ  
Norway  
Tel. +47 38 13 91 53  
Fax +47 38 13 96 91

**AUSTRALIA**  
IDENTEC SOLUTIONS  
AUSTRALIA AND NEW  
ZEALAND P/L  
Riverview Business Park 72  
Maribyrnong St, Footscray,  
3011 Australia  
Tel. +61 3 9396 8900  
Fax +61 3 9689 2493