



# i-Q350L M BROADCAST TAG



This IDENDEC SOLUTIONS' tag is intended for tracking personnel in hazardous environments such as:

- chemical plants
- petrol or gas stocks
- oil rigs

It is an ideal tool for safety of personnel.

Using advanced UHF radio frequency technology, i-Q350L M tags send data at distances of up to 150 meters (500 feet) to either a mobile (handheld) or fixed reader (interrogator).

The marker technology allows control if someone moves in or out through a gate or another specific locations. Here the inductive marker field informs the transponder about

the current location. In the same moment the transponder sends its location information several times to the reader. For this data transmission it uses its long range RFID abilities. Even after the transponder has left the marker field it transmits this data steadily at a configurable ping rate.

Due to the ultra-low power consumption and configurable ping rate (one second to 300 seconds), the i-Q350L M tag can effectively operate maintenance-free for many years.

The i-Q350L M tag is the most economical choice for basic long-range technology and is ideal for tracking personnel.

## BENEFITS

150 m (500 ft) read range - Allows the longest read-range for identification and tracking using beacon technology.

Customizable ping rate - To optimize battery consumption, dynamic appearance and RF band use.

UHF operating frequencies - Tags are available for both standard North American and European ISM band frequencies.

Non-line-of-sight data transmission - Allows tags to be identified without the need of visual contact.

Automatic transmission - Tags do not have to be "woken" — they transmit automatically.

Cost-effective - Creates the economical conditions for the usage of active high performance RFID technology to track and trace objects.

Wearability - Small form factor.

## FEATURES

- 150 m (500 ft) read range
- Customizable ping rate
- UHF operating frequencies
- Non-line-of-sight data transmission
- Automatic transmission
- Cost-effective
- Wearability

Information in this document is subject to change without notice and becomes contractual only after written confirmation by IDENDEC SOLUTIONS. "IDENDEC SOLUTIONS", "Intelligent Long Range", "ILR", "i-LINKS", "i-Q", "i-D", "i-B", "i-CARD", "i-PORT", "Solutions. It's in our name.", "Smarten up your assets." and the stylized "i" are trademarks or registered trademarks of IDENDEC SOLUTIONS, Inc. and/or IDENDEC SOLUTIONS AG.

Copyright © 2010 by IDENDEC SOLUTIONS. All rights reserved. Version 1.8 4/12/2010

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.



# i-Q350L M BROADCAST TAG

IDEN TEC SOLUTIONS delivers innovative wireless sensor technology and systems that are helping transform the way business manages industrial processes and safeguards lives.

Committed to developing industry-leading, low power and long-range sensor based solutions, IDEN TEC SOLUTIONS' SensorSMART networks have been setting the industry standard since 1999. Currently deployed on every continent throughout the globe in the Marine, Intermodal & Logistics, Oil, Gas & Mining, Construction industries as well as sought out by the world's leading system integrators and governments; IDEN TEC SOLUTIONS patented technology is helping to optimize productivity in some of the continent's most challenging situations. Robust, flexible and powerful IDEN TEC SOLUTIONS technology delivers when others cannot.

IDEN TEC SOLUTIONS is privately held, with its corporate office located in Lustenau, Austria, and North American headquarters in Dallas, Texas, along with service centers in Germany, Australia and Norway. For more information, please visit [www.identecsolutions.com](http://www.identecsolutions.com).

WARNING: Changes or modifications not expressly approved by manufacturer could void the user's authority to operate the equipment. Contents subject to change without notice.

## TECHNICAL SPECIFICATIONS

### Operating Data

Operating frequency RFID	868 MHz (EU) or 920 MHz (NA), further frequencies on request
Maximum transmission power	0.75mW (EU / NA)
Compatibility	i-PORT M 350, i-CARD CF-350
Standards/Certification	FCC Part 15 (US), ETSI EN 300 220 (EU)

### Communication Data Long-Range RFID (Response Technology)

Multiple tag handling	Up to 2,000 tags in the read zone
Read/write range response mode	Up to 5 m (16 feet), free air*
Data rate response	19.2 to 115.2 kbits/s

### Communication Data Long-Range RFID (Beacon Technology)

Read range broadcast	Up to 150 m (500 feet) free air*
Operation mode	Transmits marker information in at regular intervals
Repetition rate (ping rate)	0,5 – 300 seconds, adjustable in steps of 0,5 seconds
Data rate broadcast	115.2 kbits/s

\*The communication range depends on the antenna type, the antenna cable runs and the environmental conditions.

### Communication Data Inductive Loop (Marker)

Read range	Up to several meters
Operating frequency	125 kHz (world-wide approved)
Operation mode	Receives marker ID number and transmits marker information several times

### Electrical Data

Power supply	Lithium battery
--------------	-----------------

### Configuration

Ping rate	Configurable from 0.5 to 300 seconds in steps of 0.5 seconds
Number of Bursts	Configurable from 0 to 15

### Environmental Conditions

Operating temperature	-30 to +70 °C (-22 to +158 °F)
Shock	50 G, 3 times acc. DIN IEC 68-2-27 several times onto concrete floor from 1 m height
Vibration	3 G, 20 sine wave cycles, 5 to 150 Hz, DIN IEC 68-2-6 5 G, noise 5 to 1.000 Hz, 30 minutes DIN IEC 68-2-64

### Mechanical Data

Dimensions	56 mm x 30 mm x 14 mm
Casing	Plastics
Mass	40 g
Protection class	IP 65

### Certifications

EMC	CE (EN 300 220-1, -3; ETSI EN 301 489-1, -3),
FCC Part	15 (US), Industry Canada

## CONTACT US

### EUROPE

+43 5577 87387-0  
[sales@identecsolutions.com](mailto:sales@identecsolutions.com)

### NORTH AMERICA

1-866-402-4211 (toll free)  
[sales@identecsolutions.com](mailto:sales@identecsolutions.com)

### HEAD OFFICE

IDEN TEC SOLUTIONS AG  
Millennium Park 2  
6890 Lustenau  
Austria  
Tel. +43 5577 87387 0  
Fax +49 5577 87387 15

### GERMANY

IDEN TEC SOLUTIONS  
DEUTSCHLAND GMBH  
Hertzstrasse 10  
69469 Weinheim  
Germany  
Tel.: +49 (0)6201 9957-0  
Fax: +49 (0)6201 9957-99

### USA

IDEN TEC SOLUTIONS, INC.  
Liberty Plaza II, Suite 375  
5057 Keller Springs Rd,  
Addison, Texas 75001  
USA  
Tel: (972) 535 4144  
Fax: (469) 424-0404

### NORWAY

IDEN TEC SOLUTIONS AS  
Kartheia 3  
4626 Kristiansand  
Norway  
Tel. +47 38 00 35 30  
Fax +47 38 00 35 31

### AUSTRALIA

IDEN TEC SOLUTIONS  
AUSTRALIA AND NEW  
ZEALAND P/L  
Riverview Business Park 72  
Maribyrnong St, Footscray,  
3011 Australia  
Tel. +61 3 9396 8900